

Model	Line
POSITANO	TOURING
Article	Protection
10236-02L	S1P SRC
Sole	

Standard
EN ISO 20345:2011
Availability in stock
AVAILABLE 



PU Dual-Density SRC passed
Two-component PU sole. Outsole suitable for indoor and outdoor use. Light and comfortable. Very flexible. Self-cleaning design and highly anti-slip. SRC Antislip Standard.

Removable insole



The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A self-forming antibacterial foam layer ensures comfort and correct support of the foot.

Protection elements



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.


Type	Low Shoe
Upper	Drummed Suede Mesh
Lining	3D Air circulation 320 gr.
Anti-slip Lining	DUALMICRO
Removable insole	Flyfit
Sole	PU Dual-Density SRC passed
Toe cap	C.T.C. - Composite Toe Cap
Antiperforation	ZERO (k) ANTIPERFORATION
Size	36-48
Weight gr.	535

Working environment

Multipurpose, Logistics and Light Industry, Components and Automotive

SRC

SRC (SRA+SRB)



	FLAT	HEEL	Sole 10 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	≥ 0.32	≥ 0.28	0.39
SRB STEEL + GLYCEROL	≥ 0.18	≥ 0.13	0.19

EN ISO 20345:2011

Antistatic

WED
Wire Electricity Discharge
Strip with 4 filaments of conductive silver, ensuring proven anti-static properties of the footwear over time.

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Features



Symbols

