

Model	Line
STEPPA	ENDURANCE
Article	Protection
81001-00L	S3 SRC
Sole	

Standard
EN ISO 20345:2011
Availability in stock
AVAILABLE 



PU Dual-Density SRC passed
Two-component PU sole with anti-wear scaffold cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

Removable insole

BLOWFIT



The upper part in FLYFIT, directly in contact with the foot, means transpiration and comfort. Under the heel, a support in EVA keeps the shape and resistance over time, efficiently supporting the bodyweight.

Protection elements

ZERO(k)
ANTIPERFORATION

CT^o
Composite Toe Cap



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.

Type	Ankle boot
Upper	Full Grain leather Hydrotech Fabric of High Tenacity
Lining	3D Air circulation 320 gr.
Anti-slip Lining	DUALMICRO
Removable insole	Blowfit
Sole	PU Dual-Density SRC passed
Toe cap	C.T.C. - Composite Toe Cap
Antiperforation	ZERO (k) ANTIPERFORATION
Size	38-48
Weight gr.	720

Working environment

Multipurpose, Building, Wood-metal carpentry, Farming and Gardening

SRC

SRC (SRA+SRB)

Sole 81 PU - PU							
SRA CERAMIC + DETERGENT SOLUTION	<table border="1"> <tr> <td>FLAT</td> <td>≥ 0.32</td> <td>0.52</td> </tr> <tr> <td>HEEL</td> <td>(min. 1000 N) ≥ 0.28</td> <td>0.48</td> </tr> </table>	FLAT	≥ 0.32	0.52	HEEL	(min. 1000 N) ≥ 0.28	0.48
FLAT	≥ 0.32	0.52					
HEEL	(min. 1000 N) ≥ 0.28	0.48					
SRB STEEL + GLYCEROL	<table border="1"> <tr> <td>FLAT</td> <td>≥ 0.18</td> <td>0.23</td> </tr> <tr> <td>HEEL</td> <td>(min. 1000 N) ≥ 0.13</td> <td>0.18</td> </tr> </table>	FLAT	≥ 0.18	0.23	HEEL	(min. 1000 N) ≥ 0.13	0.18
FLAT	≥ 0.18	0.23					
HEEL	(min. 1000 N) ≥ 0.13	0.18					

EN ISO 20345:2011

Plus

STABIL ACTIVE



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Plus

dynamic Control Technology



Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.

Features



Antistatic



Strip with 4 filaments of conductive silver, ensuring proven anti-static properties of the footwear over time.

Symbols

