

Model	Line
DANCE	RITMO
Article	Protection
91195-18L	S3 SRC
Sole	

Standard
EN ISO 20345:2011
Availability in stock
AVAILABLE 



PU Dual-Density SRC passed
 PU-PU insole
 With a new formula, we have obtained a lighter and more comfortable in-between insole. The new design of the outsole has superior performances compared with standard ones after slipping tests on wet surfaces.

Removable insole



The upper part in FLYFIT, directly in contact with the foot, guarantees transpiration and comfort. The support in thermoformed EVA HD with large holes ensures correct posture and position of the foot.

Protection elements



Toecap made of aluminium with rubber, light, weighing 40% less than steel toecap. Resistant to impact of over 200J. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.

Type	Low Shoe
Upper	Full Grain Drummed leather Hydrotech Soft Full Grain Leather
Lining	3D Air circulation 320 gr.
Anti-slip Lining	DUALMICRO
Removable insole	Soft-Fit
Sole	PU Dual-Density SRC passed
Toe cap	ALU SXT
Antiperforation	ZERO (k) ANTIPERFORATION
Size	35-48
Weight gr.	480

Working environment

Multipurpose, Finishing-off building, Logistics and Light Industry, Components and Automotive
SRC

SRC (SRA+SRB)

Sole 91 PU - PU		
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL (SHOULDER) ≥ 0.28	0.54
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL (SHOULDER) ≥ 0.13	0.29

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Features



Antistatic

WED
 Wire Electricity Discharge
 Strip with 4 filaments of conductive silver, ensuring proven anti-static properties of the footwear over time.

Symbols

