



Model	Line	Standard
DEALER	TOURING	EN ISO 20345:2011
Article	Protection	Availability in stock
10349-01L	S3 SRC	AVAILABLE



Preview



Sole



PU Dual-Density SRC passed

Two-component PU sole. Outsole suitable for indoor and outdoor use. Light and comfortable. Very flexible. Self-cleaning design and highly anti-slip. SRC Antislip Standard.

Removable Insole



Anatomical and ergonomic removable insole with Flyfit, in direct contact with the foot, transpiring, and comfortable. The EVA HD perforated and thermoformed support ensures comfort and energy absorption.

Protection Elements



Toe cap made of plastic, incredibly light and resistant to impact of over 200J. New "K+ Insole", resistant to the perforation of the carpenter nail of diameter 2,8 mm, in respect to the new tests for the future.

Type	Ankle boot	
Upper	Greased Nubuk Leather Hydrotech	
Lining	3D Air circulation 320 gr.	
Antislip Lining	DUALMICRO	
Removable Insole	Blow-fit 2,0	
Sole	PU Dual-Density SRC passed	
Toe Cap	C.T.C. - Composite Toe Cap	
Anti-Perforation	K+ Anti-perforation PLUS	
Size	36-48	Weight gr. 620

Working Environment

Farming and Gardening, Logistics and Light Industry.

SRC

SRC (SRA+SRB)

	FLAT	HEEL
SRA CERAMIC + DETERGENT SOLUTION	≥ 0.32	≥ 0.28
SRB STEEL + GLYCEROL	≥ 0.18	≥ 0.13

Sole 10 PU - PU

Antistatic



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Features



Symbols

