


Model	Line	Standard
KENTUCKY	HORIZON	EN ISO 20345:2011
Article	Protection	Availability in stock
52022-14L	S3 SRC	AVAILABLE 
	Sole	PU Dual-Density SRC passed



Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

Removable insole



Antistatic absorbent in foamed latex insole

Protection elements



Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit, with compensation rubber. Stainless steel foil with acid-resistant paint.


Type	Low Shoe	
Upper	Full Grain leather Hydrotech Fabric of High Tenacity Soft Full Grain Leather	
Lining	3D Air circulation 320 gr.	
Anti-slip Lining		
Removable insole	Absorbent in foamed latex insole	
Sole	PU Dual-Density SRC passed	
Toe cap	STEEL PROTECTION	
Antiperforation		
Size	36-48	Weight gr. 610
Features		

Working environment

Multipurpose, Building, Engineering, Farming and Gardening

SRC

SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.42
	HEEL (DIN EN 12413-1) ≥ 0.28	
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.19
	HEEL (DIN EN 12413-1) ≥ 0.13	

Sole 52-53
PU - PU

EN ISO 20345:2011

Antistatic

EN ISO 20345:2011 6.2.2.2.

0,1 < MΩ < 1000

ANTI-STATIC SHOE

Plus



Thermoformed heel counter in a special material, to support the ankle.

Plus



Thermoformed heel counter in a special material, to support the ankle.

STEELPROTECTION SPUNTERBO PHTHALATEFREE SRC

Symbols

