


|           |            |                                                                                                      |
|-----------|------------|------------------------------------------------------------------------------------------------------|
| Model     | Line       | Standard                                                                                             |
| ILLINOIS  | HORIZON    | EN ISO 20345:2011                                                                                    |
| Article   | Protection | Availability in stock                                                                                |
| 52023-15L | S3 SRC     | <b>AVAILABLE</b>  |
|           | Sole       | PU Dual-Density SRC passed                                                                           |



Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

Removable insole



Antistatic absorbent in foamed latex insole

Protection elements



Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit, with compensation rubber. Stainless steel foil with acid-resistant paint.


|                  |                                                                                    |                |
|------------------|------------------------------------------------------------------------------------|----------------|
| Type             | Ankle boot                                                                         |                |
| Upper            | Full Grain leather Hydrotech<br>Fabric of High Tenacity<br>Fabric of High Tenacity |                |
| Lining           | 3D Air circulation 320 gr.                                                         |                |
| Anti-slip Lining |                                                                                    |                |
| Removable insole | Absorbent in foamed latex insole                                                   |                |
| Sole             | PU Dual-Density SRC passed                                                         |                |
| Toe cap          | STEEL PROTECTION                                                                   |                |
| Antiperforation  |                                                                                    |                |
| Size             | 36-48                                                                              | Weight gr. 650 |
| Features         |                                                                                    |                |

Working environment

Multipurpose, Building, Engineering, Farming and Gardening

SRC

**SRC (SRA+SRB)**



|                                              |                                    |      |
|----------------------------------------------|------------------------------------|------|
| SRA<br>CERAMIC<br>+<br>DETERGENT<br>SOLUTION | FLAT<br>≥ 0.32                     | 0.42 |
|                                              | HEEL<br>(DIN EN 13813-1)<br>≥ 0.28 |      |
| SRB<br>STEEL<br>+<br>GLYCEROL                | FLAT<br>≥ 0.18                     | 0.19 |
|                                              | HEEL<br>(DIN EN 13813-1)<br>≥ 0.13 |      |

Sole 52-53  
PU - PU

EN ISO 20345:2011

Antistatic

EN ISO 20345:2011 6.2.2.2.  
0,1 < MΩ < 1000  
ANTI-STATIC SHOE

Plus



Thermoformed heel counter in a special material, to support the ankle.

STEELPROTECTION SPUNTERBO PHTHALATEFREE SRC

Symbols

