



Model	Line	Standard
ANTARES	HORIZON	EN ISO 20345:2011
Article	Protection	Availability in stock
52045-10L	S3 SRC	<b>AVAILABLE</b>

Preview	Sole	PU Dual-Density SRC passed
---------	------	----------------------------



Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

**Removable Insole**



Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically designed thermoforming for exceptional comfort .

**Protection Elements**

**STEELPROTECTION**



Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit, with compensation rubber. Stainless steel foil with acid-resistant paint.

Type	Ankle boot		
Upper	Greased Nubuk Leather Hydrotech Reflex insert Soft Full Grain Leather		
Lining	Soft Full Grain Leather		
Antislip Lining	DUALMICRO		
Removable Insole	Climaction-Fit 337		
Sole	PU Dual-Density SRC passed		
Toe Cap	STEEL PROTECTION		
Anti-Perforation			
Size	36-48	Weight gr.	650

**Working Enviroment**

Building, Engineering,  
Farming and Gardening.

**SRC**

**SRC (SRA+SRB)**

			Sole 52-53 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL (EN ISO 20345:2011) ≥ 0.28	<b>0.42</b>	EN ISO 20345:2011
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL (EN ISO 20345:2011) ≥ 0.13	<b>0.19</b>	

**Plus**



Double non-slip layer of microfibre, resistant up to 200,000. Makes the footwear more comfortable, blocking the foot during use.

**Features**



**Antistatic**



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

**Plus**



**dynamicHC control**  
TECHNOLOGY

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

**Symbols**

