

Model	Line	Standard
PRISCILLA	HORIZON	EN ISO 20345:2011
Article	Protection	Availability in stock
53147-00	S2 SRC	AVAILABLE
	Sole	PU Dual-Density SRC passed



Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

Removable insole



The upper part in FLYFIT, directly in contact with the foot, means transpiration and comfort. Under the heel, a support in EVA keeps the shape and resistance over time, efficiently supporting the bodyweight.

Protection elements



Toecap made of plastic, incredibly light and resistant to impact of over 200J, very high elastic coefficient, immediately regaining the original shape without entrapping the toes. Perfect thermal isolation. Not detected by metal detector.

Type	Ankle boot	
Upper	nubuk-look leather Reflex insert Fabric of High Tenacity	
Lining	3D Air circulation 320 gr.	
Anti-slip Lining		
Removable insole	Blowfit	
Sole	PU Dual-Density SRC passed	
Toe cap	C.T.C. - Composite Toe Cap	
Antiperforation		
Size	36-42 Lady	Weight gr. 530

Working environment

Finishing-off building, Logistics and Light Industry, Food and Chemical industry, Multiurpose SRC

Sole 52-53 PU - PU

SRC (SRA+SRB)		
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.42
	HEEL (CONDUCTIVITY) ≥ 0.28	0.36
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.19
	HEEL (CONDUCTIVITY) ≥ 0.13	0.14

EN ISO 20345:2011

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Features



Symbols

