

Model	Line
STELVIO	ATLANTIDA
Article	Protection
80087-00L	S3 HRO SRC

Standard	EN ISO 20345:2011
Availability in stock	AVAILABLE 



Preview



Sole



PU-Rubber VIBRAM®-HRO-SRC

Sole with anti-wear scaff cap. Outsole in Vibram® rubber, resistant to 300° C by contact (HRO), to acids and oils. Design with self-cleaning outsole, with SRC Antislip standard.

Removable Insole



The upper part in FLYFIT, directly in contact with the foot, means transpiration and comfort. Under the heel, a support in EVA keeps the shape and resistance over time, efficiently supporting the bodyweight.

Protection Elements



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.

Type	Ankle boot		
Upper	Greased Nubuk Leather Hydrotech HT -WR Technical Fabric HT -WR Technical Fabric		
Lining	3D Air circulation 320 gr.		
Antislip Lining	DUALMICRO		
Removable Insole	Blowfit		
Sole	PU-Rubber VIBRAM®-HRO-SRC		
Toe Cap	C.T.C. - Composite Toe Cap		
Anti-Perforation	ZERO (k) ANTIPERFORATION		
Size	38-48	Weight gr.	695

Working Environment

Building, Wood-metal carpentry, Engineering, Agricoltura e Giardinaggio.

SRC

Sole 80 PU - RUBBER

SRA CERAMIC + DETERGENT SOLUTION	FLAT $\geq 0.32$	0.43
	HEEL (SRA+SRB) $\geq 0.28$	
SRB STEEL + GLYCEROL	FLAT $\geq 0.18$	0.19
	HEEL (SRA+SRB) $\geq 0.13$	

Antistatic

**WED**  
Wire Electricity Discharge  
Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Features



Symbols



Via A. Einstein, 6 - 35020 Casalserugo (PD) - ITALY - Tel. +39 049 8740771 - Fax. +39 049 8741376 - mail info@maspica.it - www.sixton.it

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Plus



Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.