



Model	Line	Standard
MONTANA	ENDURANCE	EN ISO 20345:2011
Article	Protection	Availability in stock
81156-23L	S3 WR CI SRC	AVAILABLE



Preview



Sole



PU Dual-Density SRC passed

Two-component PU sole with anti-wear scaffold cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.

Protection Elements



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.

Type	Half-knee boot
Upper	Greased Nubuk Leather Hydrotech
Lining	GenuineWool Polar
Antislip Lining	DUALMICRO
Removable Insole	Dual insulation
Sole	PU Dual-Density SRC passed
Toe Cap	C.T.C. - Composite Toe Cap
Anti-Perforation	ZERO (k) ANTIPERFORATION
Size	38-48
Weight gr.	750

Working Environment

Building, Farming and Gardening, Mountains, Ambienti freddi.

SRC

SRC (SRA+SRB)

	FLAT	Sole 81 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL ≥ 0.28	0.52
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL ≥ 0.13	0.23 0.18

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Features



Antistatic



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Symbols

