



MADE IN ITALY

Model	Line	Standard
BRESCIA	MODULAR	EN ISO 20345:2011
Article	Protection	Availability in stock
82296-05LM	S3 SRC	AVAILABLE



Preview	Sole	PU / PU ESD-plus SRC passed
---------	------	-----------------------------



Two-component PU sole, Outer - and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip. SRC Antislip standard.

Removable Insole



Anatomical and ergonomic removable insole with Flyfit, in direct contact with the foot, transpiring, and comfortable. The EVA HD perforated and thermoformed support ensures comfort and energy absorption.

Protection Elements



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.

Type	Low Shoe
Upper	Full Grain Drummed leather Hydrotech Reflex insert Soft Full Grain Leather
Lining	3D Air circulation 320 gr.
Antislip Lining	DUALMICRO
Removable Insole	Blow-fit 2,0
Sole	PU / PU ESD-plus SRC passed
Toe Cap	C.T.C. - Composite Toe Cap
Anti-Perforation	ZERO (k) ANTIPERFORATION
Size	36-48 Weight gr. 570

Working Enviroment

Finishing-off building, Logistics and Light Industry, Components and Automotive.

SRC

SRC (SRA+SRB)

SRA CESAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.47
	HEEL (DIN EN 10819) ≥ 0.28	
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.21
	HEEL (DIN EN 10819) ≥ 0.13	

EN ISO 20345:2011

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Features



Antistatic

ESD "Classe 3"
ESD footwear with high level of electrostatic dissipation. Electrical isolation between 0.1 and 100 MΩ with relative humidity of 50%.

Symbols



Via A. Einstein, 6 - 35020 Casalserugo (PD) - ITALY - Tel. +39 049 8740771 - Fax. +39 049 8741376 - mail info@maspica.it - www.sixton.it