



Model	Line	Standard
BIELLA	CRYSTAL	EN ISO 20345:2011
Article	Protection	Availability in stock
86205-00	S2 SRC	AVAILABLE



Preview



Sole



PU Dual-Density SRC passed

Two-density PU sole, light and flexible. Outsole with transverse design, to improve lengthwise and crosswise grip. SRC Antislip Standard. "Crystal" outsole for maximum grip and no-marking.

Removable Insole



The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A self-forming antibacterial foam layer ensures comfort and correct support of the foot.

Protection Elements



Toecap made of plastic, incredibly light and resistant to impact of over 200J, very high elastic coefficient, immediately regaining the original shape without entrapping the toes. Perfect thermal isolation. Not detected by metal detector.

Type	Low Shoe
Upper	Microfiber XTop
Lining	Bacteriostatic Teklife 3D
Antislip Lining	DUALMICRO
Removable Insole	Flyfit
Sole	PU Dual-Density SRC passed
Toe Cap	C.T.C. - Composite Toe Cap
Anti-Perforation	
Size	35-48
Weight gr.	450

Working Environment

Food and Chemical industry, Components and Automotive.

SRC

SRC (SRA+SRB)		
	FLAT	Sole 86 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL ≥ 0.28	0.40
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL ≥ 0.13	0.19

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Features



Antistatic

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Symbols



Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.