



Model	Line	Standard
BERGAMO	CRYSTAL	EN ISO 20345:2011
Article	Protection	Availability in stock
86206-00	S2 SRC	AVAILABLE



Preview



Sole



PU Dual-Density SRC passed

Two-density PU sole, light and flexible. Outsole with transverse design, to improve lengthwise and crosswise grip. SRC Antislip Standard. "Crystal" outsole for maximum grip and no-marking.

Removable Insole



The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A self-forming antibacterial foam layer ensures comfort and correct support of the foot.

Protection Elements



Working Environment

Food and Chemical industry, Components and Automotive.

Toecap made of plastic, incredibly light and resistant to impact of over 200J, very high elastic coefficient, immediately regaining the original shape without entrapping the toes. Perfect thermal isolation. Not detected by metal detector.

Type	Ankle boot		
Upper	Microfiber XTop Coagulated PU		
Lining	DUALMICRO		
Antislip Lining	DUALMICRO		
Removable Insole	Flyfit		
Sole	PU Dual-Density SRC passed		
Toe Cap	C.T.C. - Composite Toe Cap		
Anti-Perforation			
Size	35-48	Weight gr.	480

SRC

SRC (SRA+SRB)

	FLAT	Sole 86 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL ≥ 0.28	0.40
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL ≥ 0.13	0.19 0.24

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Features



Antistatic



Wire Electricity Discharge
Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Symbols

