

Model	Line	Standard
AVALON	POLAR	EN ISO 20345:2011
Article	Protection	Availability in stock
88056-05L	S3 HRO WR SRC	<b>AVAILABLE</b>



Preview



Sole



PU-Rubber VIBRAM®-HRO-SRC

Sole resistant to 300°C by contact. With scaff cap and compound designed with VIBRAM® for stability and grip performance. Outsole designed to strike the ground better and to improve self-cleaning. With anti-wear scaff cap.

Removable Insole



Removable insole made of a layer of FLYFIT fabric with thermoformed anatomic support in perforated E.V.A. Ergonomic insole that does not retain any water that could get into the footwear. For oil refineries and similar plants.

Protection Elements



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.

Type	Half-knee boot		
Upper	Microfiber Top HT -WR Technical Fabric		
Lining	3D Air circulation 320 gr.		
Antislip Lining	DUALMICRO		
Removable Insole	Air-Fit		
Sole	PU-Rubber VIBRAM®-HRO-SRC		
Toe Cap	C.T.C. - Composite Toe Cap		
Anti-Perforation	ZERO (k) ANTIPERFORATION		
Size	38-48	Weight gr.	800

Working Environment

Building, Farming and Gardening, Mountains, Ind. Petrolifera.

SRC

SRC (SRA+SRB)

Sole 88 PU - RUBBER

SRA CERAMIC + DETERGENT SOLUTION	FLAT $\geq 0.32$	0.34
	HEEL (EN ISO 20345:2011) $\geq 0.28$	0.31
SRB STEEL + GLYCEROL	FLAT $\geq 0.18$	0.19
	HEEL (EN ISO 20345:2011) $\geq 0.13$	0.15

Plus



Double non-slip layer of microfibre, resistant up to 200,000. Makes the footwear more comfortable, blocking the foot during use.

Features

Antistatic

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Symbols



Via A. Einstein, 6 - 35020 Casalserugo (PD) - ITALY - Tel. +39 049 8740771 - Fax. +39 049 8741376 - mail info@maspica.it - www.sixton.it