



Model	Line	Standard
BLUES	RITMO	EN ISO 20345:2011
Article	Protection	Availability in stock
91186-10L	S3 SRC	AVAILABLE



Preview



Sole



PU / PU ESD-plus SRC passed

Two-component PU sole, Outer - and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip. SRC Antislip standard.

Removable Insole



Removable insole made of highly transpirable and comfortable FLYFIT fabric, backed up by PU, open cell, shaped ergonomically. It supports the foot and absorbs the weight on the heel. The PU always ensures the same comfort over time.

Protection Elements



A new aluminium multi-thicknesses toecap, which delivers a highly performing protection where needed. Resistant to impact of over 200J. Textile anti-perforation insert. Resistant to over 1100N with zero perforation.

Type	Low Shoe
Upper	Full Grain Drummed leather Hydrotech Full Grain Drummed leather Hydrotech Soft Full Grain Leather
Lining	Resinstex (ESD class 2)
Antislip Lining	DUALMICRO
Removable Insole	Pulse
Sole	PU / PU ESD-plus SRC passed
Toe Cap	Alu SXT 2,0
Anti-Perforation	ZERO (k) ANTIPERFORATION
Size	35-48 Weight gr. 480

Working Environment

ESD Areas.

SRC

SRC (SRA+SRB)

		Sole 91 PU - PU
SRA CEMATIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL (DIN EN 10819) ≥ 0.28	0.54
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL (DIN EN 10819) ≥ 0.13	0.29

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Features



Antistatic

ESD footwear with high level of electrostatic dissipation. Electrical isolation between 0.1 and 100 MΩ with relative humidity of 50%.

Symbols

