


Model	Line	Standard
CUBAN	RITMO	EN ISO 20345:2011
Article	Protection	Availability in stock
91328-01L	S1P SRC	AVAILABLE 



Preview

Sole



Sxt pro-tech LIGHT



PU / PU ESD-plus SRC passed

Two-component PU sole, Outer - and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip. SRC Antislip standard.

Removable Insole



The upper part in FLYFIT, directly in contact with the foot, guarantees transpiration and comfort. The support in thermoformed EVA HD with large holes ensures correct posture and position of the foot.

Protection Elements



A new aluminium multi-thicknesses toecap, which delivers a highly performing protection where needed. Resistant to impact of over 200J. Textile anti-perforation insert. Resistant to over 1100N with zero perforation.

Type	Low Shoe
Upper	Microfiber Suede
Lining	3D Air circulation 320 gr.
Antislip Lining	DUALMICRO
Removable Insole	Soft-Fit
Sole	PU / PU ESD-plus SRC passed
Toe Cap	Alu SXT 2,0
Anti-Perforation	Zero(4K)-Antiperforation
Size	35-48
Weight gr.	520

Working Environment

Components and Automotive, Logistics and Light Industry.

SRC

Sole 91 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.54
	HEEL (EN ISO 20345:2011) ≥ 0.28	0.52
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.29
	HEEL (EN ISO 20345:2011) ≥ 0.13	0.23

Antistatic

WED Wire Electricity Discharge
Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Features



Symbols

