

Model	Line	Standard
CUBAN	RITMO	EN ISO 20345:2011
Article	Protection	Availability in stock
91328-03	S1 SRC	AVAILABLE



Preview

Sole

PU / PU ESD-plus SRC passed



Two-component PU sole, Outer - and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip. SRC Antislip standard.

Removable Insole



The upper part in FLYFIT, directly in contact with the foot, guarantees transpiration and comfort. The support in thermoformed EVA HD with large holes ensures correct posture and position of the foot.

Protection Elements



The result of the evolution of the latest aluminium technologies. A new multi-thicknesses toe cap, which delivers a highly performing protection where needed. Ultralight protection, keeping comfortable inner volumest

Type	Low Shoe
Upper	DUALMICRO 3D Air circulation 320 gr. Microfiber Suede
Lining	3D Air circulation 320 gr.
Antislip Lining	DUALMICRO
Removable Insole	Soft-Fit
Sole	PU / PU ESD-plus SRC passed
Toe Cap	Alu SXT 2,0
Anti-Perforation	
Size	35-48
Weight gr.	490

Working Environment

Components and Automotive, Logistics and Light Industry.

SRC

SRC (SRA+SRB)

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.54
	HEEL (SRA+SRB) ≥ 0.28	0.52
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.29
	HEEL (SRA+SRB) ≥ 0.13	0.23

Sole 91 PU - PU

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Antistatic

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Features

Symbols

