



MADE IN ITALY

Model	Line	Standard
SOUND	RITMO CROSS	EN ISO 20345:2011
Article	Protection	Availability in stock
93339-00L	S3 SRC	<b>AVAILABLE</b>



Preview	Sole	PU / PU ESD-plus SRC passed
---------	------	-----------------------------



PU double-density sole, ESD, light and comfortable. Designed mainly for outdoor use with self-cleaning reliefs. Extra-grip PU tread with SRC slip-resistant performance.

Removable Insole



The upper part in FLYFIT, directly in contact with the foot, guarantees transpiration and comfort. The support in thermoformed EVA HD with large holes ensures correct posture and position of the foot.

Protection Elements



New toecap "AluSxt 2.0" with differentiated functional thicknesses, and compensation rubber. Resistant to 200J. New "K+ Insole", resistant to the perforation of the carpenter nail of diameter 2,8 mm, in respect to the new tests for the future.

Type	Ankle boot	
Upper	Full Grain Leather Hydrotech HT -WR Technical Fabric Soft Full Grain Leather	
Lining	3D Air circulation 320 gr.	
Antislip Lining	DUALMICRO	
Removable Insole	Soft-Fit	
Sole	PU / PU ESD-plus SRC passed	
Toe Cap	Alu SXT 2,0	
Anti-Perforation	K+ Anti-perforation PLUS	
Size	35-48	Weight gr. 620

Working Environment

Finishing-off building, Wood-metal carpentry, Multipurpose.

SRC

SRC (SRA+SRB)

		Sole 93 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT $\geq 0.32$ HEEL $\geq 0.28$	0.40
SRB STEEL + GYCCEROL	FLAT $\geq 0.18$ HEEL $\geq 0.13$	0.23

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Features



Antistatic

ESD "Classe 3"  
ESD footwear with high level of electrostatic dissipation. Electrical isolation between 0.1 and 100 MΩ with relative humidity of 50%.

Symbols



Via A. Einstein, 6 - 35020 Casalserugo (PD) - ITALY - Tel. +39 049 8740771 - Fax. +39 049 8741376 - mail info@maspica.it - www.sixton.it