



Model	Line	Standard
SWING	RITMO CROSS	EN ISO 20345:2011
Article	Protection	Availability in stock
93343-00L	S3 SRC	AVAILABLE



Preview	Sole	PU / PU ESD-plus SRC passed
---------	------	-----------------------------



PU double-density sole, ESD, light and comfortable. Designed mainly for outdoor use with self-cleaning reliefs. Extra-grip PU tread with SRC slip-resistant performance.

Removable Insole



The upper part in FLYFIT, directly in contact with the foot, guarantees transpiration and comfort. The support in thermoformed EVA HD with large holes ensures correct posture and position of the foot.

Protection Elements



New toecap "AluSxt 2.0" with differentiated functional thicknesses, and compensation rubber. Resistant to 200J. New "K+ Insole", resistant to the perforation of the carpenter nail of diameter 2,8 mm, in respect to the new tests for the future.

Type	Low Shoe
Upper	Pu Coated Leather HT -WR Technical Fabric
Lining	3D Air circulation 320 gr.
Antislip Lining	DUALMICRO
Removable Insole	Soft-Fit
Sole	PU / PU ESD-plus SRC passed
Toe Cap	Alu SXT 2,0
Anti-Perforation	K+ Anti-perforation PLUS
Size	35-48
Weight gr.	580

Working Environment

Finishing-off building, Wood-metal carpentry, Building.

SRC

SRC (SRA+SRB)

		Sole 93 PU - PU
SRA CESAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL 2000x400x20 ≥0.28	0.40 0.35
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL 2000x400x20 ≥0.13	0.23 0.21

EN ISO 20345:2011

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Features



Antistatic

ESD "Classe 3"
ESD footwear with high level of electrostatic dissipation. Electrical isolation between 0.1 and 100 MΩ with relative humidity of 50%.

Symbols

