

MaxiTherm[®]

classicRange[®]

Natural Latex on a Seamless Acrylic/Polyester Liner with Patented Non Slip Grip.
Designed for general handling in wet or dry applications in cold conditions.



Technologies Inside this Glove

- Tough and flexible coating of natural latex on a seamless liner
- Brushed liner is soft and comfortable and keeps warm in cold conditions
- Non Slip Grip improves grip performance in wet applications
- Anatomically designed hand shape helps to reduce hand fatigue
- Flat dipping technology improves breathability and reduces perspiration

For a gentle glove experience



We use our HandCare[®] Program for every single ATG[®] product. Not only do we make certain that all the elements used in our manufacturing process are safe for our employees, we also wash all the gloves after the production process as a further step in ensuring cleanliness. During this laundering process, we only use water that is rain-harvested, treated and continually recycled from our own water treatment facilities. This enables us to guarantee our gloves to be "Fresh out of the pack" which is certified by Oeko-Tex[®] according Standard 100.

And if that wasn't enough our gloves are also dermatologically accredited by the Skin Health Alliance. The Skin Health Alliance seal gives, for the first time in the safety industry, professional glove users the confidence that ATG[®]'s full range of gloves are "dermatologically safe" and the science and research behind them is robust.

Of course our whole manufacturing process is in line with the requirements of the European REACH Regulation (Registration, Evaluation, Authorisation and restriction of Chemical Substances). We do not use any SVHC during our manufacturing process.



More information about HandCare[®] by ATG[®] is available at www.atg-glovesolutions.com.






MaxiTherm[®]



30-201



30-202

Design	Palm coated knitwrist	3/4 coated knitwrist
Coating	Grey	Grey
Liner	Orange	Orange
Sizes	6(XS) - 11(XXL)	8(M) - 11(XXL)
Palm thickness	2.50 mm	2.50 mm
Length		
EN 388 	1241	1241
EN 511 	X1X	X1X-
EN 407 	X2XXXX	X2XXXX--
Silicone free	No	No