


Product Data Sheet

MaxiCut® Oil™ 34-450LP

Colour – Coating	Grey
Colour – Liner	Green
Design	Palm coated knitwrist
Coating	NBR with Leather Pad
Coating texture	Leather Pad
Liner	UHMWPE-Glass-Nylon, Polyester, Spandex
Patent number	EP 1 608 808
Palm thickness	2.50 mm



Dimensions

Size Range	Size 8 (M)	Size 9 (L)	Size 10 (XL)
Total glove length (+/-10 mm)	220	230	240
Wrist length (mm)	60	70	70
Wrist width (mm)	75	80	82
Palm width (+/-3 mm)	102	107	110
Over lock colour	Orange	White	Yellow

EN test Results

Test	Notified Body	Result/Pass
EN 420: 2003 + A1: 2009	TÜV Rheinland	Yes
EN 388: 2016	TÜV Rheinland	4342C
EN 407: 2004	TÜV Rheinland	X1XXXX

If a glove due to its design and construction falls outside the scope of EN 420 in terms of hand size dimensions then this glove is classified as "fit for special purpose".



Product Data Sheet

MaxiCut® Oil™ 34-450LP

Typical Performance Values

EN 388:2016 A. Abrasion Resistance	> 8000 Cycles
EN 388:2016 B. Cut Resistance	> 5.0 index
EN 388:2016 C. Tear Resistance	> 75 newtons
EN 388:2016 D. Puncture Resistance	> 60 newtons
EN 388:2016 E. Cut Resistance ISO	≥ 10 Newton

HandCare®

Skin Health Alliance Dermatologically Accredited	Yes
REACH compliant	Yes
Oeko-Tex® 100	Certified
Sanitized®	Yes



Special features

Silicone free	No
---------------	----

Packaging

Pairs per poly bag	12
Poly bags per carton	6
Carton count	72
Carton dimensions (mm)	500 x 295 x 270



Product Data Sheet

MaxiCut® Oil™ 34-450LP

Weight

Size Range	Size 8 (M)	Size 9 (L)	Size 10 (XL)
Glove weight / Pair (+/-6 gram)	50	56	60
Gross Weight (Kg)	4.7	5.2	5.5
Carton Weight (Kg)	1	1	1
Net Weight (Kg)	3.7	4.2	4.5

Issue date: 07.06.2019

