



EN ISO 20345:2011



HORIZON
GAMMA
52421-01L

S3 SRC

Size: 36-48
Weight: 760 gr.

Fit: 10,5

Working Environment:
Building, Wood-metal carpentry,
Farming and Gardening,
Engineering



FEATURES

UPPER
Greased Nubuk Dakar Leather
Hydro
Reflex insert

LINING
Soft Full Grain Leather Hydro
Double non-slip layer of
microfibre, resistant up to 200,000
cycles. Makes the footwear more
comfortable, blocking the foot
during use.

INSOLE
Climaction-Fit 337

TOE CAP
Steel Toe Cap

RESISTANCE TO PERFORATION
Steel Plate

TYPE
Ankle boot

SOLE
PU DUAL-DENSITY SRC
Two-component PU sole with self-
cleaning pattern, extremely flexible
for various places of use, both
indoor and outdoor, with SRC
Antislip Standard.

TECHNOLOGIES

Removable Insole **337**
climaction fit

Removable anatomic and ergonomic
insole. Absorbent and transpiring
open-cell foam support. Keeps feet
fresh. Specifically-designed
thermoforming for exceptional
comfort.



Protection elements
STEEL PROTECTION

Steel toecap, with anti-corrosion
paint. Protection of over 200J.
Comfortable fit. Stainless steel Plate
resistant puncture with acid-resistant
paint.




Lateral stability
dynamic HC control
technology

Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.



Torsional stability
STABIL•ACTIVE

It supports the heel bone, the instep
and tarsal joints, without altering
energy absorption. A support for the
natural movement of the foot; it
provides comfort and greater
stability.




Electrical features
WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber,
ensuring proven anti-static properties
of the footwear over time.



Other
DUAL MICRO DWTWICBO

Double non-slip layer of microfibre,
resistant up to 200,000 cycles. Makes
the footwear more comfortable,
blocking the foot during use.



SRC (SRA+SRB)

SOLE 52 - 53 PU - PU		
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.36 0.42
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19 0.14

EN ISO 20344:2011