



EN ISO 20345:2011



POLAR  
**STELVIO**  
88087-17L

**S3 HRO HI WR SRC**

**Size:** 38-48  
**Weight:** 865 gr.

**Fit:** 11

**Working Environment:**  
Building, Farming and Gardening,  
Mountains, Wood-metal  
carpentry



## FEATURES

### UPPER

Greased Nubuk Dakar Leather  
Hydro  
Reflex insert  
Full Grain leather Hydro

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Blow-fit 2.0

### TOE CAP

CTC- Composite Toe Cap

### RESISTANCE TO PERFORATION

Zero(K) Perforation resistant

### TYPE

Ankle boot

### SOLE

**PU-RUBBER VIBRAM®-HRO-SRC**

Sole resistant to 300°C by contact.  
With scaff cap and compound  
designed with VIBRAM® for  
stability and grip performance.  
Outsole designed to strike the  
ground better and to improve self-  
cleaning. With anti-wear scaff cap.

## TECHNOLOGIES

### Removable Insole

**blow fit 2.0**

Anatomical and ergonomic removable  
insole with Flyfit, in direct contact  
with the foot, transpiring, and  
comfortable. The E.V.A. HD perforad  
and thermoformed support ensures  
comfort and energy absorption



### Protection elements

**ZERO(k)**  
ANTIPERFORATION



Toecap made of plastic, incredibly  
light and resistant to impact of over  
200J, elastic. Athermic. Not detected  
by metal detector. Fabric anti-  
perforation foil. Resistant to over  
1100 N with zero perforation.



### Lateral stability

**dynamic HC control**  
technology

Ergonomic rigid internal structure. It  
houses the heel into the right seat,  
adjusting the foot support and control  
of the ankle sideways movements. It  
keeps the foot tight to the shoe,  
allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic  
material. It stabilizes the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.



### Electrical features

**WED**

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber,  
ensuring proven anti-static properties  
of the footwear over time.



### Other

**DUALMICRO**

Double non-slip layer of microfibre,  
resistant up to 200,000 cycles. Makes  
the footwear more comfortable,  
blocking the foot during use.



## SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.34
	HEEL (CONTACT ANGLE °) ≥0.28	
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.19
	HEEL (CONTACT ANGLE °) ≥0.13	

EN ISO 20344:2011