



**EN ISO 20344:2011** 

**SKIPPER LADY**  
**CIMA**  
**95398-02L**

**S3 SRC**

**Size:** 35-42 Lady  
**Weight:** 420 gr.

**Fit:** 11

**Working Environment:**  
 Logistics and Light Industry,  
 Components and Automotive, ESD Areas



**FEATURES**

**UPPER**  
 Digitex Hydro Airy  
 MicroFiber Suede with Pro-tech  
 SXT light

**LINING**  
 Breezy 3D, two-layers  
 combination

**ANTISLIP LINING**  
 DUALMICRO

**INSOLE**  
 Five 4 Fit "lady"

**TOE CAP**  
 Alu SXT 2.0 Toe cap

**RESISTANCE TO PERFORATION**  
 Textile resistant to 3.0 mm nail - X  
 Method

**TYPE**  
 Low Shoe

**SOLE**  
**PU DUAL-DENSITY SRC**  
 Double density PU outsole with  
 tread designed mainly for indoor  
 use. Self-cleaning design and  
 highly non-slip grip. SRC Antislip  
 standard.



**TECHNOLOGIES**

**Removable Insole**  
**FIVE 4 FIT**  
 LADY

Highly breathable and absorbent  
 anatomic insole. Multilayer structure  
 to take advantage of the peculiarities  
 of each component. Dry and with a  
 comfortable memory foam "pillow"



**Protection elements**  
**K+** ANTI PERFORATION PLUS  
**alu-sxt 2.0** aluminium

Aluminium toe cap "Alu Sxt 2.0" with  
 differentiated functional  
 thicknesses, and compensation  
 rubber. Resistant to 200J. And Non  
 metallic "K+ Insole", tested with  
 carpenter nail of diameter 2.8 mm,  
 with pyramidal trunk tip



**Lateral stability**  
**dynamic HC control**  
 technology

Ergonomic rigid internal structure. It  
 houses the heel into the right seat,  
 adjusting the foot support and control  
 of the ankle sideways movements. It  
 keeps the foot tight to the shoe,  
 allowing the perfect fit.



**Torsional stability**  
**STABIL ACTIVE**

Support made of rigid plastic  
 material. It stabilizes the heel bone,  
 the instep and tarsal joints, without  
 altering energy absorption. A support  
 for the natural movement of the foot;  
 it provides comfort and greater  
 stability.



**Electrical features**  


ESD footwear discharge static  
 electricity and avoid damaging  
 surrounding objects; they are  
 designed in compliance with the  
 following standards: IEC EN  
 61340-5-1:2016 - IEC EN  
 61340-4-3:2018 - IEC EN  
 61340-4-5:2018.

**Other**  
**DUALMICRO**  
 DUALMICRO

Double non-slip layer of microfibre,  
 resistant up to 200,000 cycles. Makes  
 the footwear more comfortable,  
 blocking the foot during use.

**SRC (SRA+SRB)**



		SOLE 95 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.38
	HEEL (CONTACT ANGLE °) ≥0.28	0.34
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.21
	HEEL (CONTACT ANGLE °) ≥0.13	0.24

EN ISO 20344:2011