



EN ISO 20345:2011



TOURING  
**DEALER BOOT**  
10349-01L

**S3 SRC**

**Size:** 36-48  
**Weight:** 620 gr.

**Working Environment:**  
Farming and Gardening, Logistics and Light Industry, Multipurpose, Building



**FEATURES**

**UPPER**  
Greased Nubuk Dakar Leather Hydro

**LINING**  
Soft Full Grain Leather Hydro  
3D Air circulation 320 gr.

**ANTISLIP LINING**  
DUALMICRO

**INSOLE**  
Blow-fit 2.0

**TOE CAP**  
CTC- Composite Toe Cap

**RESISTANCE TO PERFORATION**  
Textile resistant to 3.0 mm nail - X Method

**TYPE**  
Ankle boot

**SOLE**  
**PU DUAL-DENSITY SRC**  
Two-component PU sole. Outsole suitable for indoor and outdoor use. Light and comfortable. Very flexible. Self-cleaning design and highly anti-slip. SRC Antislip Standard.

**TECHNOLOGIES**

**Removable Insole**  
**blow fit 2.0**

Anatomical and ergonomic removable insole with Flyfit, in direct contact with the foot, transpiring, and comfortable. The E.V.A. HD perforad and thermoformed support ensures comfort and energy absorption



**Protection elements**



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Not detected by metal detector. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Flexible and comfortable



**Lateral stability**  
**dynamic HC control technology**

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

**Torsional stability**  
**STABIL ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



**Other**



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



**SRC (SRA+SRB)**



<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	<b>0.39</b>
	HEEL (CONTACT ANGLE °) ≥0.28	
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18	<b>0.19</b>
	HEEL (CONTACT ANGLE °) ≥0.13	

EN ISO 20345:2011