



EN ISO 20345:2011



RITMO  
**BLUES**  
91186-10L

**S3 SRC**

**Size:** 35-48  
**Weight:** 540 gr.

**Fit:** 11

**Working Environment:**  
ESD Areas, Components and  
Automotive, Special, Multipurpose



## FEATURES

**UPPER**  
Drummed leather Hydro

**LINING**  
Resistex® Carbon

**ANTISLIP LINING**  
DUALMICRO

**INSOLE**  
Five 4 Fit

**TOE CAP**  
Alu SXT 2.0 Toe cap

**RESISTANCE TO PERFORATION**  
Zero(K) Perforation resistant

**TYPE**  
Low Shoe

**SOLE**  
**PU / PU ESD-PLUS SRC**  
Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

## TECHNOLOGIES

**Removable Insole**  
**FIVE4FIT**

Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



**Protection elements**  
**ZERO(k)**  
ANTIPERFORATION **alu-sxt2.0**  
aluminium

A new aluminium multi-thicknesses toecap, which delivers a highly performing protection where needed. Resistant to impact of over 200J. Non Metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.



**Lateral stability**  
**dynamic HC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



**Torsional stability**  
**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

**Other**

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### SRC (SRA+SRB)

		SOLE 91 PU - PU
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	<b>0.54</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	<b>0.29</b>
		<b>0.23</b>

EN ISO 20344:2011