sixton SAFETY SHOES peak



EN ISO 20345:2011

RITMO

DANCE

91195-18L

S3 SRC

Size: 35-48
Weight: 540 gr.

Fit: 11

Working Enviroment:
Finishing-off building, Logistics and Light Industry, Components and Automotive

FEATURES

UPPER
Drummed leather Hydro

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Five 4 Fit

TOE CAP
Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION
Zero(K) Perforation resistant

TYPE
Low Shoe

SOLE
PU DUAL-DENSITY SRC
Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.

S E FO A WRU P SRC

SRC (SRA+SRB)

SOLE 91
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.54
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.52
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.29
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.23

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole

FIVE4FIT

Highly breathable and absorbent anatomic insole.Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"

Protection elements

ZERO(k) ANTIPERFORATION

alu-sxt 2.0 aluminium

A new aluminium multi-thicknesses toecap, which delivers a highly performing protection where needed. Resistant to impact of over 200J. Non Metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.

Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Electrical features

WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Other

DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.

Maspica S.p.A. Via Einstein,6 - 35020 Casalserugo - Padova / Italy - Cap. Soc. 1.050.000 i.v. - cod. fisc. e Reg. Imp. 04009100282 p. iva IT04009100282
C.C.I.A.A./R.E.A.354572 tel. +39 049 8740771 fax +39 049 8741376 www.sixton.it - info@maspica.it

Questo documento è di proprietà di Maspica SpA, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale