



EN ISO 20345:2011



TOURING DEALER BOOT 10349-00L

S3 SRC
Size: 36-48
Weight: 620 gr.

Working Enviroment:
 Farming and Gardening, Logistics
 and Light Industry, Multipurpose,
 Building


FEATURES

UPPER

Greased Nubuk Dakar Leather Hydro

LINING

 Soft Full Grain Leather Hydro
 3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Blow-fit 2.0

TOE CAP

CTC- Composite Toe Cap

RESISTANCE TO PERFORATION

 Textile resistant to 3.0 mm nail - X
 Method

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY SRC

 Two-component PU sole. Outsole
 suitable for indoor and outdoor use.
 Light and comfortable. Very
 flexible. Self-cleaning design and
 highly anti-slip. SRC Antislip
 Standard.

TECHNOLOGIES

Removable Insole

**2.0
blow fit**

 Anatomical and ergonomic removable
 insole with Flyfit, in direct contact
 with the foot, transpiring, and
 comfortable. The E.V.A. HD perforad
 and thermoformed support ensures
 comfort and energy absorption


Protection elements


**RESISTANT
TO 3.0 mm.
NAILS**


Composite Toe Cap

 Toecap made of plastic, incredibly
 light and resistant to impact of over
 200J, elastic. Not detected by metal
 detector. Non metal perforation
 resistant Insert to over 1100 N with a
 3.0 mm truncated cone nail. Flexible
 and comfortable


Lateral stability

**dynamic HC control
technology**

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability

STABIL•ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features

WED

Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


Other

**DUALMICRO
DUALMICRO**

 Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.


SRC (SRA+SRB)


 SOLE 10
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE 7°) ≥0.28	0.39
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE 7°) ≥0.13	0.19

EN ISO 20344:2011