



EN ISO 20345:2011



ENDURANCE
MONTANA
81156-00L

S3 SRC

Size: 36-48
Weight: 710 gr.

Fit: 11

Working Environment:
Building, Farming and Gardening,
Oil industry



FEATURES

UPPER

Full Grain-Anilina Leather-Hydro

INSOLE

Dual insulation

TOE CAP

CTC- Composite Toe Cap

RESISTANCE TO PERFORATION

Zero(K) Perforation resistant

TYPE

Half-knee Boot

SOLE

PU DUAL-DENSITY SRC

Two-component PU sole with anti-wear scaffold cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.



SRC (SRA+SRB)

		SOLE 81 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.52 0.48
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.23 0.18

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



Protection elements

ZERO(k)
ANTIPERFORATION



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.



Lateral stability

dynamic **HC control**
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features

WED

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other

DUAL MICRO DWTWICBO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.