



EN ISO 20345:2011 

ENDURANCE
CORVARA
81087-15L

S3 WR SRC

Size: 36-48
Weight: 710 gr.

Fit: 11


Working Environment:
Building, Wood-metal carpentry,
Farming and Gardening,
Multipurpose





FEATURES

- UPPER**
Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm
Reflex insert
Full Grain leather Hydro
- LINING**
3D Air circulation 320 gr.
- ANTISLIP LINING**
DUALMICRO
- INSOLE**
Blow-fit 2.0
- TOE CAP**
CTC- Composite Toe Cap
- RESISTANCE TO PERFORATION**
Zero(K) Perforation resistant
- TYPE**
Ankle boot

SOLE
PU DUAL-DENSITY SRC
Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.



SRC (SRA+SRB)

				SOLE 81 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.52	0.48	
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.23	0.18	EN ISO 20345:2011

TECHNOLOGIES

Removable Insole
blow fit 2.0

Anatomical and ergonomic removable insole with Flyfit, in direct contact with the foot, transpiring, and comfortable. The E.V.A. HD perforad and thermoformed support ensures comfort and energy absorption



Protection elements
ZERO(k)
ANTIPERFORATION 

Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.



Lateral stability
dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability
STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features
WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
DUALMICRO DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.