



EN ISO 20345:2011 

HORIZON
VEGA
52045-02L

S3 SRC

Size: 36-48
Weight: 680 gr.

Fit: 10,5

Working Environment:
Multipurpose, Building,
Engineering, Farming and
Gardening

FEATURES

UPPER
Pigmented Leather-Hydro 1,8-2,0 mm
Reflex insert

LINING
3D Air circulation 320 gr.
Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.

INSOLE
Basic

TOE CAP
Steel Toe Cap


RESISTANCE TO PERFORATION
Steel Plate

TYPE
Ankle boot

SOLE
PU DUAL-DENSITY SRC
Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.



SRC (SRA+SRB)

		SOLE 52 - 53 PU - PU	
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.36	0.42
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19	0.14

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole

BASIC
Antistatic absorbent in foamed latex insole



Protection elements

STEEL PROTECTION
Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit. Stainless steel Plate resistant puncture with acid-resistant paint.




Lateral stability

dynamic HC control technology
Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE
It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features

WED
Wire Electricity Discharge
Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other

DUAL MICRO DUAL MICRO
Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.