



EN ISO 20345:2022



DIVVENTURE MARMOLADA

70539-05L

S7S FO *CI SC LG SR

Size: 36-48

Weight: 750 gr.

Fit: 11

Working Environment:

Building, Wood-metal carpentry, Oil industry, Farming and Gardening



FEATURES

UPPER

 Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm
Reflex insert

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP


Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation recycled PS

TYPE

Ankle boot


PU - PU

SOLE 70

SLIP RESISTANCE

EN ISO 20345:2022

BASIC CERAMIC WITH NAILS		FORWARD HEELSLIP ≥ 0.31	0,39	ESD 0-3 mm
FORWARD FOREPART SLIP ≥ 0.36	0,42			
SR CERAMIC WITH GLYCERINE		FORWARD HEELSLIP ≥ 0.19	0,20	ESD 0-3 mm
BACKWARD FOREPART SLIP ≥ 0.22	0,31			

Protection elements


Composite toecap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable


Lateral stability


Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.


Torsional stability


Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.


Electrical features


ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other


The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user.

